



prisma25ST

BiLevel-ST therapy device



BiLevel-ST therapy with innovative setting concept (SCOPES)

Maximum flexibility for indication-specific pre-settings (SCOPES): prisma25ST leaves room for individually tailored solutions. Perfect for patients with obstructive, mixed or complex sleep apnea with comorbidities. Equipped with automatic backup frequency, apnea differentiation by FOT and many process and comfort supporting features, prisma25ST provides reliable, effective and whisper-quiet BiLevel-ST therapy Made in Germany.

Major features

- Ventilation modes: CPAP, APAP, BiLevel S, autoS, BiLevel S/T, autoS/T, BiLevel T
- High level of safety due to auto back up frequency or high fixed back up frequency
- Optionally with autoTRiLevel principle
- SCOPES for indication-specific pre-settings
- Optional auto Trigger (Trigger IN)
- High resolution therapy data for up to 14 days and detailed statistics for 366 days
- Therapy software prismaTS for data analysis and remote control
- With SD card and USB port
- Telemedicine connection via modem for prisma CLOUD
- Eight clearly identified analog signals for PSG feed
- Comfort functions such as autoSTART-STOP and softSTART
- Heated breathing tube prismaHYBERNITE
- Easy-to-use accessories

prismaLINE. A platform to trust

prismaLINE is the intelligent system solution for treatment of respiratory disorders.

The prismaLINE represents a new dimension in operating convenience. The combination of a large monitor (touch screen or LED) and smart Graphical User Interface allows more intuitive and faster use than ever before.

This exceptional operating concept is found throughout the prismaLINE portfolio. Every prismaLINE device provides the user with ideal support for all kinds of work processes and for connectivity and accessories too.

prismaLINE offers the right device for every type of therapy in Löwenstein Medical quality: precise, reliable and unheard-of stillness.

prismaLINE: Synonymous with modern sleep therapy Made in Germany.



Accessories



prismaAQUA – WM 29680
Humidifier



prismaCONNECT
WM 29670



prismaPSG – WM 29690
PSG Module

Accessories (not shown)

Inverter 24 V, lorry – WM 24617

Inverter 12 V, car – WM 24616

prismaTS – WM 93335

Therapy software, complete with USB data cable

Bacteria filter – WM 24476

Set of 12 pollen filters – WM 29652

Breathing tube, Ø 22 mm – WM 24445

Breathing tube, Ø 15 mm – WM 29988

Autoclavable breathing tube, Ø 22 mm – WM 24667

Heated breathing tube,

prismaHYBERNITE, Ø 15 mm – WM 29083

prismaHYBERNITE, Ø 22 mm – WM 29067

prisma CHECK, SpO₂ module – WM 29390

Modem for prisma CLOUD – WM 31240

You'll find more information about our therapy solutions, accessories and mask systems at loewensteinmedical.de

Technical data

Product class as per Directive 93/42/EEC	IIa	Modes	CPAP, APAP, BiLevel S, auto S, BiLevel S/T, autoS/T, BiLevel T
Dimensions (W x H x D)	170 x 135 x 180 mm	Mean sound pressure/ Operation as per ISO 80601-2-70	about 26.5 dB(A) at 10 hPa (corresponds to sound pressure of 34.5 dB(A))
Weight	about 1.4 kg	CPAP operating pressure range	4 to 20 hPa
Temperature range • Operation: • Storage:	+5 °C to +40 °C -25 °C to +70 °C	BiLevel operating pressure range	4 to 25 hPa
Permitted humidity, operation and storage	rel. humidity 10 % to 95 %, no condensation	Relative inspiration time: Ti/Tset	25% to 67%
Air pressure range	700 – 1060 hPa corresponds to altitude of 3000 meters	Trigger	auto or can be set at three levels
Diameter of breathing tube	22 mm or 15 mm	Pressure increase speed	can be set at three levels
Electric rating	max. 40 VA	Back up frequency	0 bpm, 5 to 35 bpm, auto
System interface	12 V DC max. 10 VA	Pressure accuracy	< 20 hPa ± 0.6 hPa, ≥ 20 hPa ± 0.8 hPa
Power consumption in • Operation (therapy): • Standby:	230 V 115 V 0.11 A 0.22 A 0.036 A 0.019 A	Peak flow as per ISO 80601-2-70, mode BiLevel, without humidifier	4.0 hPa 235 l/min 10.5 hPa 225 l/min 17.0 hPa 215 l/min 23.5 hPa 200 l/min 25.0 hPa 195 l/min
Classification as per EN 60601-1-1 • Type of protection from electric shock: • Level of protection from electric shock: • Protection from damaging ingress of water and solids:	protection class II type BF IP21	Stability of the dynamic pressure (short-term accuracy) for 10 breaths/min as per ISO 17510-1:2007 with use of the 22-mm tube.	7.0 hPa Δp ≤ 0.24 hPa 10.0 hPa Δp ≤ 0.28 hPa 13.5 hPa Δp ≤ 0.3 hPa 20.0 hPa Δp ≤ 0.4 hPa
Alarms	leak and disconnection		

Device description

prisma25ST

Ord. Nr.

WM 29920



Please refer to the current price list.

Löwenstein Medical Technology
Kronsaalsweg 40, 22525 Hamburg
Germany
T: +49 40 54702-0
F: +49 40 54702-461
info@loewensteinmedical.de
www.loewensteinmedical.de

